

Specifications

	IPC6852SR-X44U				
Camera					
Sensor	1/2.8", progressive scan,2.0megapixel, CMOS				
Lens	5 ~ 220 mm , AF automatic focusing and motorized zoom lens				
Digital Zoom	16				
Optical Zoom	44				
DORI Distance	Lens	Detect(m)	Observe(m)	Recognize(m)	Identify(m)
	5mm	77.6	31	15.5	7.8
	220mm	3413.8	1365.5	682.8	341.4
Angle of View (H)	60.6°~ 1.8°				
Angle of View (V)	34.8°~0.8°				
Angle of View (O)	74.5°~2.1°				
Shutter	Auto/Manual; shutter time: 1/6 s ~ 1/100000 s				
Minimum Illumination	Colour: 0.001 lux (F1.2, AGC ON) 0 lux with IR				
Iris	Auto/Manual; F1.2 ~ F3.5				
Day/Night	IR-cut filter with auto switch (ICR)				
Digital noise reduction	2D/3D DNR				
S/N	>52dB				
IR Range	Up to 250m(820 ft)				
WDR	120dB				
Video					
Video Compression	Ultra 265,H.265, H.264, MJPEG				
H.264 code profile	Baseline profile, Main Profile, High Profile				
Frame Rate	Main Stream:2MP (1920×1080):Max. 60 fps; Sub Stream:2MP (1920×1080):Max. 60 fps; Third Stream: D1 (720×576): Max. 60 fps				
HLC	Supported				
BLC	Supported				
EIS	Supported				
OSD	Up to 8 OSDs				
Privacy Mask	Up to 24 areas				
ROI	Up to 8 areas				
Motion Detection	Up to 4 areas				
Smart					
Behavior Detection	Intrusion, cross line, motion detection, Auto tracking				
Intrusion	Enter and loiter in a pre-defined virtual region				
cross line	Cross a pre-defined virtual line				
motion detection	Moving within a pre-defined virtual region				
auto tracking	Tracking the specified target				
Recognition	Face detection、 Audio detection				
Intelligent Identification	Defocus, Scene Change				
Statistical Analysis	People counting				
General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication				
Audio					
Audio Compression	G.711				
Two-way audio	Supported				
Suppression	Supported				
Sampling Rate	8 KHZ				
Storage					
Edge Storage	Micro SD, up to 128GB				
Network Storage	ANR				
Network					
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP				
Compatible Integration	ONVIF(Profile S, Profile G), API				
Pan & Tilt					
Pan Range	360° (endless)				
Pan Speed	0.1°/s ~ 240°/s				
	Preset speed: 300°/s				
Tilt Range	-15° ~ +90° (auto reverse)				
Tilt Speed	0.1° ~ 160°/s				
	Preset speed: 240°/s				
Number of Presets	1024				
Patrol	Preset patrol, route patrol, recorded patrol				
Home Position	Supported				
Interface					
Audio I/O	Audio cable				
	1 Input: impedance 35 kΩ; amplitude 2 V [p-p]				
	1 Output: impedance 600 Ω; amplitude 2 V [p-p]				
Alarm I/O	2 / 1				
Serial Port	1 RS485				
Network	1 RJ45 10M/100M Base-TX Ethernet				
Video Output	1 BNC, impedance 75 Ω; amplitude 1 V [p-p]				
General					
Power	24 V±25% AC (Default), 24 V±25% DC				
	Power consumption:16 ~56W				
Dimensions(ØxH)	Φ270mm×496.7mm(Φ10.6" x 19.6")				
Weight	9.69kg(21.4lb)				
Working Environment	-40℃~70℃(-40°F ~ 158°F), Humidity:10%~95% RH(non-condensing)				
Ingress Protection	IP66				
Heat	Built-in Heater and Temperature control system				
Reset Button	Supported				